



FLUIDOS REFRIGERANTES TABELA PRESSÃO X TEMPERATURA

TEMPERATURA	PRESSÃO						
	PRO-134	R600a	PRO-410	R290a	PRO-22	PRO-404	PRO-32
	psig	psig	psig	psig	psig	psig	psig
-44	-3.0	-11	0.9	1	1.1	1.1	1.9
-40	-2.0	-10	1.3	1.4	1.5	1.6	2.5
-36	-1.0	-9.6	3.2	3.4	3.5	3.8	6.5
-32	1.7	-8.5	7.8	8.1	8.3	9.1	9.5
-28	3.0	-7.2	10.5	10.7	10.9	11.5	11.8
-24	3.8	-5.8	16.4	16.7	17.0	17.6	18.0
-20	7.1	-4.1	19.7	20.1	20.5	21.3	21.4
-16	10.3	-2.3	27.1	27.6	28.2	29.2	29.3
-12	16.1	-0.1	31.3	31.8	32.5	33.9	34.1
-8	20.4	2.3	35.7	36.3	37.0	37.1	38.2
-4	25.2	5.0	45.6	46.3	47.2	48.5	48.7
0	32.0	8.1	54.8	55.7	56.8	56.3	56.8
4	37.0	11.5	62.8	63.9	65.2	65.6	66.8
8	45.0	15.3	68.4	69.5	70.1	71.5	72.4
12	55.2	19.5	74.4	75.6	77.1	76.1	77.0
16	68.8	24.1	87.8	89.2	90.1	92.1	91.0
20	75.0	29.1	106.5	108.2	110.3	110.7	111.7
24	87.0	34.7	116.5	118.3	120.6	120.2	121.0
28	95.4	40.8	137.6	139.7	142.5	141.3	143.0
36	122.3	54.5	159.4	161.9	165.2	163.8	164.0
40	141.7	62.3	183.3	186.1	190.0	189.2	192.5
44	162.1	70.7	210.2	213.4	217.7	215.8	218.0
48	179.4	80.0	224.5	227.9	232.5	229.6	233.0
52	204.0	89.6	239.0	242.8	247.7	244.1	248.1
56	212.0	100.5	271.0	275.8	281.3	277.3	285.5
60	226.0	111.3	287.8	292.2	298.0	294.4	301.0
64	231.3	123.4	323.9	328.9	336.5	330.8	332.5
68	248.8	136.2	343.1	348.4	355.4	350.3	355.0
72	254.1	144.0	363.0	368.7	376.0	370.5	365.0

TABELA DE COMPATIBILIDADE DE LUBRIFICANTES

	ÓLEO MINERAL	ALQUIBENZENO	POE	PAG
PRO-22	SIM	SIM	SIM	SIM
PRO-410	SIM	SIM	SIM	SIM
PRO-134	SIM	SIM	SIM	SIM
PRO-404	SIM	SIM	SIM	SIM
PRO-32	SIM	SIM	SIM	SIM